

432MHS6W



Products → Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe
→ Switched Interlocked Socket Outlets

General Information

Extended Product Type:	432MHS6W
Product ID:	2CMA167865R1000
EAN:	7392696678650
Catalog Description:	Switched interlocked socket-outlet, 6h, 32A, IP67, 3P+N+E
Long Description:	Switched Interlocked Socket Outlet, horisontal, earthing sleeve position 6h, rated current 32A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

EAN:	7392696678650
Minimum Order Quantity:	1 piece
Country of Origin:	Czech Republic (CZ)

Dimensions

Product Net Width:	169 mm
Product Net Height:	129 mm
Product Net Length:	137 mm
Product Net Depth / Length:	137 mm
Product Net Weight:	0.76 kg

Container Information

Package Level 1 Width:	135 mm
Package Level 1 Depth / Length:	140 mm
Package Level 1 Height:	200 mm
Package Level 1 Gross Weight:	0.84 kg
Package Level 1 EAN:	7392696678650
Package Level 1 Units:	1 piece
Package Level 2 Units:	174 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CMC700005D0001_F
Declaration:	2CMC700005D0001_F
Environmental Information:	2CMC000057M0000
RoHS Information:	2CMC700005D0001_F

SEMKO Certificate: 1515100

Additional Information

Additional Information:	3P+N+E
Cable Cross-Section:	2.5 ... 10 mm ²
Cable Entry Position:	Top and bottom
Cable Outlets Per Side:	1xØ25
Color:	Red
Connection Type:	Screw clamp
Degree of Protection:	IP67
Enclosure Material:	Thermoplastic polyester (PBT)
Frequency (f):	50 Hz 60 Hz
Function:	Switched interlocked socket outlet, horizontal
Housing Material:	Thermoplastic (PBT)
Invoice Description:	Ind. P&S#432MHS6W
Mounting Holes:	146x91
Mounting Type:	Horizontal
Number of Poles:	5
Order Multiple:	1 piece
Product Main Type:	CMHS
Product Name:	Industrial Switched Interlocked Socket Outlet
Protection Type:	Switched Interlocked
Rated Current (I _n):	32 A
Rated Voltage (U _r):	200/346 ... 240/415 V
Recommended Screw Driver:	PH2
RoHS Date:	L23
Standards:	IEC 60309-1 IEC 60309-2 IEC 60309-4
Sub-Function:	Cable entry, knock-outs Ø25mm/M25
Suitable For:	Switched Interlocked Socket Outlets, Horizontal
Suitable for Product Class:	Industrial Plugs and Sockets

Classifications

eClass:	27440510
E-nummer:	2416957
UNSPSC:	39120000

