

**STE 140 (601401500) Jigsaw**  
(220-240 V / 50 - 60 Hz); metaBOX 145

Order no. 601401500  
EAN 4007430212207



Product may differ from image



- Extremely powerful jigsaw with VTC-Electronics for fast cuts into soft wood of up to 140 mm deep
- Extremely handy due to small body circumference and soft-grip surface
- Precise and material-matched sawing due to the variable stroke rate, pendulum stroke and low-lying saw blade guidance with spring support
- Metabo Quick for tool-free saw blade change and with automatic ejection
- Selectable chip blowing function ensures free view of cutting line
- Vario Tacho Constamatic (VTC) Full-wave Electronics for work with materials requiring customised stroke rates, which remain constant under load
- Long service life thanks to optimum gear and motor design and robust die-cast aluminium gear housing
- With metaBOX, the intelligent solution for transport and storage

## Technical data

### Characteristics

|                              |                  |
|------------------------------|------------------|
| Rated input power            | 750 W            |
| Output power                 | 420 W            |
| Cutting depth wood           | 140 mm / 5 1/2 " |
| Cutting depth NF metal       | 35 mm / 1 3/8 "  |
| Cutting depth sheet steel    | 10 mm / 3/8 "    |
| Swivel range from / to:      | - 45 / + 45 °    |
| Pendulum stroke levels       | 4                |
| Strokes in idle              | 1000 - 3100 rpm  |
| Saw blade stroke             | 26 mm / 1 1/32 " |
| Weight (without power cable) | 2.5 kg / 5.5 lbs |
| Cable length                 | 4 m / 13 ft      |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Sawing wood                  | 13.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Sawing metal                 | 10 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 90 dB(A)  |
| Sound power level (LwA)      | 101 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Extraction Nozzles  
Chip Guard Plates  
Hexagonal wrench  
metaBOX 145  
Protective glass  
Plastic guard plate